LEDcure Pincure Z - Aircooled



Innovative, High Powered UV LED Pinning

Pincure Z UV LED offers a powerful solution in a compact and lightweight package for ultimate high speed pinning between inkjet print heads. The air cooling exhaust is from the top of the lamp head, away from any adjacent print heads.

The proven optics of the original Pincure model (which eliminates the risk of UV light damage to the print head nozzle plates) has been further enhanced, and in Pincure Z is now housed within a clever design which prohibits media contact and contamination to the lens.

The complete modular concept allows end to end mounting of 120mm and 80mm modules in every configuration to unlimited length. Up to 960mm (8 x 120mm Pincure Z heads) can be daisy-chained together with only one incoming electrical cable.

All of ITL's extensive UV LED product range have a life expectancy of 20,000 + operating hours as standard, ITL UV LED curing solutions are fitted with field replaceable modules offering extended service life and is covered by a comprehensive warranty backed by global support direct from Integration Technology and through its strategic partner IST Metz.

The Pincure system is also available in a watercooled Pincure C version.

For high speed applications requiring a higher peak intensity or greater dose, ITL offer a variaty of final cure and more powerfull Pinning UV-LED systems.

Pincure Z Standard Features	
Wavelength	395nm (Std), 365nm, 385nm, 405nm
Power	3 W/cm² *
Dimensions (LxWxH)	80mm/120mm x 20mm x 234mm
Emmission window	80mm x 7mm 120mm x 7mm
Operation Temperature	<40°C
Weight	80mm head: 400gms 120mm head: 550gms
Cooling	Aircooled with changeable fan filters
Cable	up to 15m supply cable (highflex), up to 8 heads can be daisy chained
Protocol	Standard I/O or serial bus
Addressability	40mm steps **
Options	Smart hub DC Powersupply

* @395nm measured at the emitting window using an EIT Power Map UW sensor

** Addressability patented by European patent: EP1599340/ GB2399162, Cross licence with Lumen Dynamics Group Inc. U.S. Patent No. 6,683,421



Head Office: Integration Technology Ltd., Heyford Park, Upper Heyford, Oxfordshire, OX25 5HA, United Kingdom Tel.: +44 (0) 1869 233611, Fax: +44 (0) 1869 233599, mail@uvintegration.com

Integration Technology North America dbohn@uvintegration.com Integration Technology Korea jyoon@uvintegration.com

For more information: www.uvintegration.com

Integration Technology (China) Ltd. syang@uvintegration.com

Integration Technology Japan ykatsuta@uvintegration.com Integration Technology Latin America edsel@uvintegration.com.br